

工位数S	转位角度	规格	静扭力 Ts (kgf-m)	动扭力 (kgf-m) 分割回转速 N (rpm)								摩擦 扭力 Tx(kgf-m)
				50	100	150	200	300	400	500	700	
2	270	7D	11.3	4.3	3.5	3.1	2.9	2.5	2.3	2.2	2.0	0.12
	180		11.3	5.2	4.2	3.7	3.4	3.0	2.8	2.6	2.4	0.5
	270		15.5	5.9	4.8	4.3	3.9	3.5	3.2	3.0	2.7	0.4
	180		12.6	5.7	4.6	4.1	3.8	3.3	3.1	2.9	2.6	0.4
	270		14.8	5.5	4.5	3.9	3.6	3.2	2.9	2.7	2.5	0.3
	180		5	2.3	1.9	1.6	1.5	1.3	1.2	1.1	1.0	0.3
	270		5.7	2.1	1.7	1.5	1.4	1.3	1.1	1.1	1.0	0.2
	90		12.5	8.2	6.7	5.9	5.4	4.8	4.4	4.1		0.5
	120		14.6	8.2	6.6	5.9	5.4	4.8	4.4	4.1	3.7	0.5
	150		16.1	8.0	6.5	5.8	5.3	4.7	4.3	4.0	3.6	0.4
6	180		17.2	7.8	6.4	5.6	5.2	4.6	4.2	3.9	3.6	0.4
	210		17.9	7.6	6.2	5.5	5.0	4.5	4.1	3.8	3.5	0.4
	240		18.5	7.5	6.1	5.4	4.9	4.4	4.0	3.7	3.4	0.4
	270		18.8	7.3	5.9	5.2	4.8	4.2	3.9	3.6	3.3	0.4
	300		19.1	7.1	5.8	5.1	4.7	4.1	3.8	3.6	3.2	0.3
	330		19.4	6.9	5.6	5.0	4.6	4.1	3.7	3.5	3.1	0.3
	90		12.6	6.9	6.3	5.6	5.2	4.6	4.2	3.9	3.5	0.4
	120		14.2	7.4	6.2	5.5	5.0	4.4	4.1	3.8	3.5	0.4
	150		15.2	7.4	6.0	5.3	4.9	4.3	3.9	3.7	3.3	0.3
	180		16.8	8.0	6.5	5.8	5.3	4.7	4.3	4.0	3.6	0.3
8	210		17.3	7.7	6.3	5.6	5.1	4.5	4.2	3.9	3.5	0.3
	240		17.6	7.5	6.1	5.4	5.0	4.4	4.0	3.8	3.4	0.3
	270		17.8	7.3	5.9	5.2	4.8	4.3	3.9	3.7	3.3	0.3
	300		18	7.1	5.8	5.1	4.7	4.1	3.8	3.6	3.2	0.3
	330		18.1	6.9	5.6	5.0	4.6	4.0	3.7	3.5	3.1	0.3
	90		25	3.0	2.5	2.2	2.0	1.8	1.6	1.5		0.3
	120		5.5	2.9	2.4	2.1	1.9	1.7	1.6	1.5	0.54	0.3
	150		5.7	2.8	2.3	2.0	1.8	1.6	1.5	1.4	1.3	0.2
	180		5.9	2.7	2.2	1.9	1.8	1.6	1.4	1.3	1.2	0.2
	210		6	2.6	2.1	1.9	1.7	1.5	1.4	1.3	1.2	0.2
10	240		6	2.5	2.0	1.8	1.6	1.5	1.3	1.2	1.1	0.2
	270		6.1	2.4	2.0	1.7	1.6	1.4	1.3	1.2	1.1	0.2
	300		6.1	2.3	1.9	1.7	1.5	1.4	1.3	1.2	1.1	0.2
	330		6.1	2.3	1.9	1.6	1.5	1.3	1.2	1.1	1.0	0.2
	90		2.7	1.6	1.3	1.1	1.1	0.9	0.9			0.2
	120		2.8	1.5	1.2	1.1	1.0	0.9	0.8	0.8		0.2
	150		2.9	1.4	1.2	1.0	0.9	0.8	0.8	0.7		0.2
	180		3	1.4	1.1	1.0	0.9	0.8	0.7	0.7	0.6	0.2
	210		3	1.3	1.1	0.9	0.9	0.8	0.7	0.7	0.6	0.2
	240		3	1.3	1.0	0.9	0.8	0.7	0.7	0.6	0.6	0.2
12	270		3.1	1.2	1.0	0.9	0.8	0.7	0.7	0.6	0.6	0.2
	300		3.1	1.2	1.0	0.9	0.8	0.7	0.6	0.6	0.5	0.2
	330		3.1	1.2	0.9	0.8	0.8	0.7	0.6	0.6	0.5	0.5

工位数S	转位角度	规格	静扭力 Ts (kgf-m)	动扭力 (kgf-m) 分割回转速 N (rpm)							摩擦 扭力 Tx(kgf-m)
				50 100 150 200 300 400 500 700							
				12.6	6.9	6.3	5.6	5.2	4.6	4.2	3.9
16	90*		12.6	6.9	6.3	5.6	5.2	4.6	4.2	3.9	0.7
	120*		15.1	8.6	7.0	6.2	5.6	5.0	4.6	4.3	3.9
	150*		16.1	8.3	6.7	6.0	5.5	4.8	4.4	4.2	3.8
	180*		16.8	8.0	6.5	5.8	5.3	4.7	4.3	4.0	3.6
	210*		17.3	7.7	6.3	5.6	5.1	8.9	8.2	7.6	3.5
	240*		17.6	7.5	6.1	5.4	5.0	4.4	4.0	3.8	3.4
	270*		17.8	7.3	5.9	5.2	4.8	4.3	3.9	3.7	3.3
	300*		18	7.1	5.8	5.1	4.7	4.1	3.8	3.6	3.2
	330*		18.1	6.9	5.6	5.0	4.6	4.0	3.7	3.5	3.1
	90*		5	3.0	2.5	2.2	2.0	1.8	1.6		0.3
20	120*		5.5	2.9	2.4	2.1	1.9	1.7	1.6	1.5	0.3
	150*		5.7	2.8	2.3	2.0	1.8	1.6	1.5	1.4	0.2
	180*		5.9	2.7	2.2	1.9	1.8	1.6	1.4	1.3	1.2
	210*		6	2.6	2.1	1.9	1.7	1.5	1.4	1.3	1.2
	240*		6	2.5	2.0	1.8	1.6	1.5	1.3	1.2	1.1
	270*		6.1	2.4	2.0	1.7	1.6	1.4	1.3	1.2	1.1
	300*		6.1	2.3	1.9	1.7	1.5	1.4	1.3	1.2	1.1
	330*		6.1	2.3	1.9	1.6	1.5	1.3	1.2	1.1	1.0
	90*		2.7	1.6	1.3	1.1	1.1	0.9			0.2
	120*		2.8	1.5	1.2	1.1	1.0	0.9	0.8		0.2
24	150*		2.9	1.4	1.2	1.0	0.9	0.8	0.8	0.7	0.2
	180*		3	1.4	0.7	1.0	0.9	0.8	0.7	7.2	6.5
	210*		3	1.3	1.1	0.9	0.9	0.8	0.7	0.7	0.2
	240*		3	1.3	1.0	0.9	0.8	0.7	0.7	0.6	0.6
	270*		3.1	1.2	1.0	0.9	0.8	0.7	0.7	0.6	0.6
	300*		3.1	1.2	1.0	0.9	0.8	0.7	0.6	0.6	0.5
	330*		3.1	1.2	0.9	0.8	0.8	0.7	0.6	0.6	0.5
	90●		5	3.0	2.5	2.2	2.0	1.8	1.6	1.5	0.3
	120●		5.5	2.9	2.4	0.85	1.9	1.7	1.6		0.3
	150●		5.7	2.8	2.3	2.0	1.8	1.6	1.5	1.4	0.2
30	180*		5.9	2.7	2.2	1.9	1.8	1.6	1.4	1.3	0.2
	210●		6	2.6	2.1	1.9	1.7	1.5	1.4	1.3	0.2
	240●		6	2.5	2.0	1.8	1.6	1.5	1.3	1.2	0.2
	270●		6.1	2.4	2.0	1.7	1.6	1.4	1.3	1.2	0.2
	300●		6.1	2.3	1.9	1.7	1.5	1.4	1.3	1.2	1.1
	330●		6.1	2.3	1.9	1.6	1.5	1.3	1.2	1.1	1.0
	90●		2.7	1.6	1.3	1.1	1.1	0.9	0.9		0.2
	120●		2.8	1.5	1.2	1.1	1.0	0.9			0.2
	150●		2.9	1.4	1.2	1.0	0.9	0.8	0.8		0.2
	180●		3	1.4	1.1	1.0	0.9	0.8	0.7		0.2
36	210●		3	1.3	1.1	0.9	0.9	0.8	0.7	0.7	0.2
	240●		3	1.3	1.0	0.9	0.8	0.7	0.7	0.6	0.2
	270●		3.1	1.2	1.0	0.9	0.8	0.7	0.7	0.6	0.2

工位数S	转位角度	规格	静扭力 Ts (kgf-m)	动扭力 (kgf-m) 分割回转速 N (rpm)								摩擦 扭力 Tx(kgf-m)	
				50 100 150 200 300 400 500 700									
				3.1	1.2	1.0	0.9	0.8	0.7	0.6	0.6	0.5	
36	300●		3.1	1.2	1.0	0.9	0.8	0.7	0.6	0.6	0.6	0.5	0.2
	330●		3.1	1.2	0.9	0.8	0.8	0.7	0.6	0.6	0.6	0.5	0.2
40	90☆		5	3.0	2.5	2.2	2.0	1.8	1.6	1.5			0.3
	120☆		5.5	2.9	2.4	2.1	1.9	1.7					0.3
	150☆		5.7	2.8	2.3	2.0	1.8	1.6	1.5				0.2
	180☆		5.9	2.7	2.2	1.9	1.8	1.6	1.4	1.3			0.2
	210☆		6	2.6	2.1	1.9	1.7	1.5	1.4	1.3			0.2
	240☆		6	2.5	2.0	1.8	1.6	1.5	1.3	1.2			0.2
	270☆		6.1	2.4	2.0	1.7	1.6	1.4	1.3	1.2	1.1		0.2
	300☆		6.1	2.3	1.9	1.7	1.5	1.4	1.3	1.2	1.1		0.2
	330☆		6.1	2.3	1.9	1.6	1.5	1.3	1.2	1.1	1.0		0.2
	90☆		2.7	1.6	1.3	1.1	1.1	0.9	0.9				0.2
	120☆		2.8	1.5	1.2	1.1	1.0	0.9					0.2
	150☆		2.9	1.4	1.2	1.0	0.9	0.8					0.2
48	180☆		3	1.4	1.1	1.0	0.9	0.8	0.7				0.2
	210☆		3	1.3	1.1	0.9	0.9	0.8	0.7				0.2
	240☆		3	1.3	1.0	0.9	0.8	0.7	0.7	0.6			0.2
	270☆		3.1	1.2	1.0	0.9	0.8	0.7	0.7	0.6			0.2
	300☆		3.1	1.2	1.0	0.9	0.8	0.7	0.6	0.6			0.2
	330☆		3.1	1.2	0.9	0.8	0.8	0.7	0.6	0.6			0.2
7D													

备注： ○ : 1DWELL * : 2DWELL ● : 3DWELL ☆ : 4DWELL